

LIQUEFACTION-SUSCEPTIBILITY AND SEISMIC SOIL-TYPE MAPS OF ANCHORAGE, ALASKA

Award 01HQGR0006

R. A. Combellick

Alaska Division of Geological & Geophysical Surveys

794 University Ave., Suite 200

Fairbanks, Alaska 99709

907-451-5007, Fax 907-451-5050

Email rod@dnr.state.ak.us; URL <http://www.dggs.dnr.state.ak.us>

Program Element I

Keywords: surficial deposits, liquefaction, site effects, seismic zonation

INVESTIGATIONS

An existing published map (Harding-Lawson Associates, 1979) portrays ground-failure susceptibility in the Anchorage area and has been in use by the Municipality of Anchorage for several years as the basis of an earthquake-related zoning ordinance. Depiction of hazards zones on the map was based on earthquake-induced ground displacements that were initiated largely by sensitive-clay failures during the 1964 great Alaska earthquake and on empirical data regarding seismic behavior of geologic units portrayed on a generalized geologic map of Anchorage (Schmoll and Dobrovolsky, 1972). Subsurface data were not used in preparation of the Harding-Lawson map, consequently liquefaction susceptibility of sand and silt was not evaluated. With the geotechnical borehole database recently compiled by the Alaska Division of Geological & Geophysical Surveys (ADGGS), we have acquired the kinds of data (soil classification, standard penetration tests, sample analytical data, groundwater level) necessary to evaluate liquefaction susceptibility of deposits in the Anchorage area. We have completed the initial data compilation and will use the data in conjunction with revised simplified procedures (Seed and Idriss, 1971, 1982; Idriss, 1997; Youd, 1997) to produce a liquefaction-susceptibility map of Anchorage at 1:25,000 scale. We do not plan to re-map susceptibility to sensitive-clay failure at this time because there is insufficient city-wide borehole data on clay properties to improve significantly on the Harding-Lawson map.

Geotechnical engineers and building officials in the Anchorage area have expressed the need for a map showing seismic soil types (site classes) that can be used in conjunction with the Uniform Building Code to estimate the seismic design requirements of most small structures. While site-specific analysis is necessary for large or critical facilities, the requirements of the Anchorage code can be satisfied with reliable map data for most other structures. Because the soil-profile classifications of the Uniform Building Code have been replaced with the NEHRP-recommended site-classes (Building Seismic Safety Council, 1995), we are preparing a 1:25,000-scale map of the NEHRP site classes for Anchorage. We are collaborating with investigators at the University of Alaska to classify seismic site classes on the basis of surface-measured shear-wave velocity profiles in Anchorage (Biswas and others, 1993; Biswas and Dravinski, 1994; Nath and others, 1997) and a small number of available downhole shear-wave velocity tests. We are also using the borehole data we have compiled (standard penetration data, soil types, layer

surficial-geologic map units. Additionally, because the transition between seismic site classes C and D is diffuse, we depict this transition area as a band on the map to which we assign site class C/D. We are presently incorporating user comments we have received into final revisions to the map before submitting it for publication. The publication process will include a technical peer review.

Now that compilation of the borehole database is complete, we are evaluating and compiling appropriate data from it for the purpose of performing liquefaction-susceptibility analyses using the simplified Seed-Idriss methods. The results of these analyses will be used to generate a liquefaction-susceptibility map of the Anchorage area.

REPORTS PUBLISHED

- Combellick, R.A., 1999, Simplified geologic map and cross sections of central and east Anchorage, Alaska: Alaska Division of Geological & Geophysical Surveys Preliminary Interpretive Report 1999-1, 12 p., 2 sheets, scale 1:25,000.
- Combellick, R.A., Sink, K.D., and Weems, S.M., 1998, Geotechnical database and 3-D modeling of subsurface geology in Anchorage, Alaska [abs.]: Association of Engineering Geologists Program with Abstracts, 41st Annual Meeting, Seattle, Washington, p. 84.

REFERENCES CITED

- Biswas, N.N., Succarieh, M., Liu, H., Dravinski, M., Saikia, C., Papageorgiou, A., and Mahdyiar, M., 1993, Seismic microzonation: Metropolitan Anchorage, Alaska: funded proposal to the Alaska Science and Technology Foundation, ASTF 91-2-125.
- Biswas, N.N., and Dravinski, M., 1994, Determination of shear wave velocities in near surface geologic formations in Anchorage, Alaska: funded USGS/NEHRP proposal, University of Alaska Fairbanks, award 1434-95-G-2520.
- Building Seismic Safety Council, 1995, NEHRP recommended provisions for seismic regulations for new buildings, 1994 edition: Washington, Federal Emergency Management Agency report 222A, part 1 (Provisions), p. 4-7.
- Combellick, R.A., 1999, Simplified geologic map and cross sections of central and east Anchorage, Alaska: Alaska Division of Geological & Geophysical Surveys Preliminary Interpretive Report 1999-1, 12 p., 2 sheets, scale 1:25,000.
- Harding-Lawson Associates, 1979, Geotechnical hazards assessment study, Municipality of Anchorage: Harding-Lawson Associates job no. 5502,009.08.
- Idriss, I.M., 1997, Evaluation of liquefaction potential and consequences: Historical perspective and updated procedures, *in* D'Orazio, Tim, ed., unpublished proceedings, 3rd Seismic Short Course on Evaluation and Mitigation of Earthquake Induced Liquefaction Hazards, San Francisco State University.
- Nath, S.K., Chatterjee, D., Biswas, N.N., Dravinski, M., Cole, D.A., Papageorgiou, A., Rodriguez, J.A., and Poran, C.J., 1997, Correlation study of shear wave velocity in near surface geological formations in Anchorage, Alaska: *Earthquake Spectra*, v. 13, no. 1, p. 55-75.

- Schmoll, H.R., and Dobrovolsky, Ernest, 1972a, Generalized geologic map of Anchorage and vicinity, Alaska: U.S. Geological Survey Miscellaneous Geologic Investigations Map I-787-A, scale 1:24,000.
- Seed, H.B., and Idriss, I.M., 1971, Simplified procedure for evaluating soil liquefaction potential: Journal of the Soil Mechanics and Foundations Division, ASCE, v. 97, no. SM9, p. 1249-1273.
- Seed, H.B., and Idriss, I.M., 1982, Ground motions and soil liquefaction during earthquakes: Berkeley, Earthquake Engineering Research Institute, 134 p.
- Udike, R.G., 1986, Engineering-geologic maps of the Government Hill area, Anchorage, Alaska: U.S. Geological Survey Miscellaneous Investigations Map I-1610, scale 1:4,800.
- Udike, R.G., and Ulery, C.A., 1986, Engineering-geologic map of southwest Anchorage, Alaska: Alaska Division of Geological & Geophysical Surveys Professional Report 89, scale 1:15,840.
- Youd, T.L., 1997, Preliminary report from NCEER workshop on evaluation of liquefaction resistance of soils, *in* D'Orazio, Tim, ed., unpublished proceedings, 3rd Seismic Short Course on Evaluation and Mitigation of Earthquake Induced Liquefaction Hazards: San Francisco State University.

LIQUEFACTION-SUSCEPTIBILITY AND SEISMIC SOIL-TYPE MAPS OF ANCHORAGE, ALASKA

Award 01HQGR0006

R. A. Combellick

Alaska Division of Geological & Geophysical Surveys

794 University Ave., Suite 200

Fairbanks, Alaska 99709

907-451-5007, Fax 907-451-5050

Email rod@dnr.state.ak.us; URL <http://www.dggs.dnr.state.ak.us>

Program Element I

Keywords: surficial deposits, liquefaction, site effects, seismic zonation

NONTECHNICAL SUMMARY

The purpose of this project is to produce two maps of Anchorage to help mitigate earthquake hazards. One is a seismic site-class map, a draft of which we have completed and distributed to geotechnical users for comments. The map is designed to be used with the International Building Code to help estimate design requirements for resisting earthquake-shaking damage. The second product is a map showing areas susceptible to liquefaction during strong earthquakes. This map, currently under development, will help identify areas that should be avoided or where special designs must be used to prevent damage from earthquake-induced ground failures.